






290 gr/m²,
50% HPPE 50% Polyester,
Abrasion Resistant,
Denim Woven Fabric



Sample



ArGiyim Denim Kursun - 6032
Navy

ArGiyim Denim Kursun - 6033
Black


Description

50% HPPE (high performance polyethylene) 50% polyester denim twill fabric. The front side of the fabric is polyester which is ultra durable for sun light, the back side of the fabric is hppe which provides extra abraision resistance for motorcyclist's cloth. ArGiyim Denim Kursun can be used on abraision resistant cloths. EN 388 certified as cut proof. EN 17092 certified as motorcyclist norms.

Technical Parameters

Name	Values	Standards
Fiber	50% HPPE (PE) 50% Polyester (PES)	EN ISO 2076
Yarn	13/1 Ne + 30/2 Ne	EN ISO 2060
Weight	290 ±20 gr/m ²	EN ISO 3081
Width	1600 ±20 mm	EN ISO 3932
Tensile Strength	Warp>2500N; Weft>3500N	EN ISO 13934-1
Tear Strength	Warp>150N; Weft>40N	EN ISO 13937-2
Dimensional Change	-3%<Length<+3%;-3%<Width<+3%	EN ISO 5077
Rubbing Fastness	4-5	EN ISO 105 X12
Perspiration Fastness	4-5	EN ISO 105 E04
Washing Fastness	4-5	EN ISO 105 C06
Dry Cleaning Fastness	4-5	EN ISO 105 D01
Hypochlorite Fastness	4-5	EN ISO 105 N01
Peroxide Fastness	4-5	EN ISO 105 N02
Hot Press Fastness	4-5	EN ISO 105 X11
pH	4.0-7.0	EN ISO 3071
Azo Test	No Azo Colorants.	EN ISO 14362-1
Application	Motorcyclist Cloth	
Quality Management	Done	ISO 9001
Cut Proof	Done	EN 388
Motorcyclist	Done	EN 17092