



55 gr/m<sup>2</sup>, 100% Polyester,  
2\*2 Mesh Fabric



Sample



## Description

Arof Mesh 2\*2 is 100% polyester, 50-60 gr/m<sup>2</sup> warp knitted 2\*2 mesh fabric.

Due to mesh structure it can provide both safety for the material and transparency. It can be used as a bag's side pocket, parka interlining, raincoat back fabric and car seat's back cover.

## Technical Parameters

Name	Values	Standards
Fiber	100% Polyester (PES)	TS EN ISO 1833
Yarn	68 Denier	EN ISO 2060
Weight	55±5 gr/m <sup>2</sup>	TS EN 12127
Width	1600 ±20 mm	TS EN 1773
Bursting strength	> 500 kPa (kN/m <sup>2</sup> )	TS EN 13938-1
Dimensional Change	-5%<Length<+5%;-5%<Width<+5%	TS EN ISO 5077
Abrasion Resistance	@50000	TS EN 530
Rubbing Fastness	4	EN ISO 105 X12
Perspiration Fastness	4-5	EN ISO 105 E04
Washing Fastness	4-5	EN ISO 105 C01
Dry Cleaning Fastness	4-5	EN ISO 105 D01
Hypochlorite Fastness	4-5	EN ISO 105 N01
Hot Press Fastness	4-5	EN ISO 105 X11
Light Fastness	4-5	EN ISO 105 B02
pH	6.2	EN ISO 3071
Azo Test	No Azo Colorants.	EN ISO 14362-1
Application	Mesh for Bag, Car Seat, Raincoat	
Quality Management	Done	ISO 9001

**Arof Mesh 2\*2 - 4368**  
**High Visible Yellow**



**Arof Mesh 2\*2 - 4360**  
**High Visible Green**



**Arof Mesh 2\*2 - 4359**  
**High Visible Orange**



**Arof Mesh 2\*2 - 4369**  
**White**



**Arof Mesh 2\*2 - 4370**  
**Black**



**Arof Mesh 2\*2 - 5169**  
**Navy**



The technical data on this guide is given for information and correct at the time of design. It can be changed without prior notice.